

MSDS - Material Safety Data Sheet**Product Name: LIQUID WRENCH DRY LUBE WITH CERFLON****MSDS No.: L512****I. Basic Information:****Manufacturer:** RADIATOR SPECIALTY COMPANY**Address:** 600 RADIATOR ROAD**City, ST Zip:** INDIAN TRAIL, NC 28079**Country:****Contact:** Robert Geer**Information Telephone Number:** 704-684--181 1**Emergency Contact:** Rocky Mountain Poision Control Center**Emergency Telephone Number:** 303-623-5716**Emergency Restrictions:****Product Name:** LIQUID WRENCH DRY LUBE WITH CERFLON**MSDS No.:** L512**Issue Date:** 04/02/2009**Supersedes Date:** 12/06/2007**II. Hazards Identification:****EMERGENCY OVERVIEW**

Danger: Extremely Flammable. Harmful or fatal if swallowed. Eye and skin irritant. Contents under pressure.

Level 3 Aerosol

OSHA Regulatory Status

This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).

Potential Health Effects**Route(s) of Entry:**

Absorption, Inhalation, and Ingestion.

Health Hazards (Acute and Chronic):

Chronic: High levels damage the nervous system initially producing a lack of feeling in the extremities and possibly progressing to a more severe nerve damage.

Signs and Symptoms:

Eye Contact: Irritant. Prolonged contact may cause conjunctivitis.

Skin Contact: Irritant. Defatting of tissue, dermatitis may occur.

Inhalation: Irritant to mucous membranes. Repeated exposure may cause narcosis, dizziness, respiratory or lung irritation.

Ingestion: HARMFUL OR FATAL IF SWALLOWED.

Medical Conditions Generally Aggravated by Exposure:

N/D

Other Health Warnings:

Vomiting and subsequent aspiration into the lungs may lead to chemical pneumonia and pulmonary edema which is a potentially fatal condition.

Potential Environmental Effects

Not Available

III. Composition/Information on Ingredients:

Chemical Name	CAS No.	% Range	Trade Secret
Acrylic acid	79-10-7	0.1 - 1.0	
Heptane	142-82-5	15.0 - 40.0	
Isopropanol	67-63-0	30.0 - 60.0	
n-Butyl Acetate	123-86-4	0.1 - 1.0	
Polytetrafluoroethylene	9002-84-0	0.1 - 1.0	
Propane	74-98-6	15.0 - 40.0	

MSDS - Material Safety Data Sheet

Product Name: *LIQUID WRENCH DRY LUBE WITH CERFLON*

MSDS No.: L512

IV. First Aid Measures:

Emergency and First Aid Procedures:

Eye Contact: Flush eyes with clean water for 15 minutes while lifting eyelids. Get prompt medical attention.

Skin Contact: Wash with soap and water thoroughly. If adverse effects persist, get prompt medical attention. Launder contaminated clothing before reuse.

Inhalation: Remove to fresh air. If breathing becomes difficult give oxygen and get prompt medical attention. If breathing stops, give artificial respiration and get prompt medical attention.

Ingestion: DO NOT INDUCE VOMITING! Call Poison Control Center, physician, or hospital emergency room immediately. Aspiration of vomitus into the lungs can cause pneumonitis, which can be fatal.

Note to Physicians:

N/E

V. Fire Fighting Measures:

Suitable Extinguishing Media:

Water Fog, Foam, Carbon Dioxide, Dry Chemical

Unsuitable Extinguishing Media:

Do not use forced water stream as this could cause the fire to spread.

Products of Combustion:

Normal products of combustion, smoke, carbon dioxide, carbon monoxide.

Protection of Firefighters:

Wear self-contained positive pressure breathing apparatus and protective clothes. Use shield to protect from rupturing and venting containers. At elevated temperatures containers may vent, rupture or burst, even violently

VI. Accidental Release Measures:

Personal Precautions:

Persons not wearing protective equipment should be excluded from area of spill until clean-up has been completed.

Environmental Precautions:

Prevent run-off to sewers, streams, or other bodies of water. If run-off occurs, notify proper authorities as required that a spill has occurred. Run off to sewer may create fire or explosion hazard.

Methods for Containment:

Dike or contain spill and absorb with inert materials (sand, sawdust, absorbent sweeping compounds, rags, etc).

Methods for Cleanup:

Using a non-metallic scoop, place contaminated material into an approved chemical waste container. Where possible, vacuum spilled liquid using an explosion proof vacuum to recover material.

Other Information:

Eliminate all ignition sources. Prevent run-off to sewers, streams, or other bodies of water. If run-off occurs, notify proper authorities as required that a spill has occurred.

VII. Handling and Storage:

Handling Precautions:

Do not used in confined area without proper ventilation. Contact lenses may cause further damage in case of splash into eye. KEEP AWAY FROM CHILDREN AND ANIMALS! Danger extremely flammable.

Storage Precautions:

Do not use or store near fire, sparks, or open flame. Do not puncture or incinerate container. Exposure to temperatures above 120° may cause container to vent, rupture, or burst.

VIII. Exposure Controls/Personal Protection:

MSDS - Material Safety Data Sheet**Product Name: LIQUID WRENCH DRY LUBE WITH CERFLON**

MSDS No.: L512

Chemical Name	OSHA PEL	ACGIH TLV	Other Limits
Polytetrafluoroethylene	N/D	N/D	Not Available
Isopropanol	400 ppm	400 ppm	Not Available
Acrylic acid	N/E	N/E	Not Available
Heptane	500 ppm	400 ppm	Not Available
n-Butyl Acetate	150 ppm	150 ppm	Not Available
Propane	N/E	1000 ppm	Not Available

Engineering Controls:

See Section above for applicable exposure limits. If TLV is exceeded, wear NIOSH approved respirator.

Personal Protective Equipment:

For prolonged exposure wear protective safety glasses, gloves, and apron.

IX. Physical and Chemical Properties:**Boiling Point:** <100° F**Boiling Range:** N/D**Solubility in Water:** Insoluble**Flash Point:** < 0°F**Odor Threshold:** N/D**Vapor Density (AIR = 1):** N/D**pH Range:** N/A**Decomposition Temp:** N/D**Lower Explosive Limit:** N/E**Specific Gravity (H2O = 1):** 0.76**Other Information:** VOC Content: 94.5%**Melting Point:** N/A**Freezing Point:** N/A**Evaporation Rate (Butyl Acetate = 1):** > 1.0**Flash Point Method:** Calculated**Appearance and Odor:** Clear liquid with white suspended particles with hydrocarbon odor.**Vapor Pressure (mm Hg.):** N/D**Partition Coefficient:** N/D**Auto-Ignition Temp:** N/D**Upper Explosive Limit:** N/E**X. Stability and Reactivity:****Stability:**

Stable

Conditions to Avoid:

Heat, sparks or flames. Also see incompatible materials listed below

Incompatible Materials:

Avoid contact with strong oxidizers

Hazardous Decomposition Products:

Normal products of combustion, smoke, carbon dioxide, carbon monoxide.

Possibility of Hazardous Reactions:

Will not occur

XI. Toxicological Information:

N/D

MSDS - Material Safety Data Sheet**Product Name: LIQUID WRENCH DRY LUBE WITH CERFLON****MSDS No.: L512****XII. Ecological Information:**

N/D

XIII. Disposal Considerations:

DISPOSAL: This container may be recycled in aerosol recycling centers when empty. Before offering for recycling, empty the can by using the product according to the label. DO NOT PUNCTURE! If recycling is not available, wrap the container and discard in the trash. Dispose of unused product in accordance with all local, state government and federal laws and regulations.

XIV. Transport Information:**Shipping Name:** Not Available**DOT Hazard Class:** Not Available**DOT Subsidiary Hazard Class:** Not Available**UN/NA#:** Not Available**Packing Group:** Not Available**Transportation Information:**

DOT Hazard Class: ORM-D

Shipping Name: Consumer Commodity

The DOT description is provided to assist in the proper shipping classification of this product and may not be suitable for international and air shipping purposes.

ICAO/IATA (US)

UN Number: UN1950

Shipping Name: Aerosols

Class: 2.1

International:

ICAO/IATA

UN Number: UN1950

Shipping Name: Aerosols

Class: 2.1

IMDG

UN Number: UN1950

Shipping Name: Aerosols

Class: 2.1

EmS: F-D, S-U

XV. Regulatory Information:

SARA 313 Reportable Chemicals:

USA TSCA: All components of this material are listed on the US TSCA Inventory.

State RTK Chemicals:

Heptane 142-82-5

Isopropyl Alcohol 67-63-0

Acrylic Acid 79-10-7

n-Butyl Acetate 123-86-4

Propane 74-98-6

MSDS - Material Safety Data Sheet

Product Name: LIQUID WRENCH DRY LUBE WITH CERFLON


MSDS No.: L512

XVI. Other Information:

Chemical State: Liquid Gas Solid

Chemical Type: Pure Mixture


Hazard Category:
 Acute Chronic Fire
 Pressure Reactive



Additional Manufacturer Warnings:

Do not used in confined area without proper ventilation. Contact lenses may cause further damage in case of splash into eye. KEEP AWAY FROM CHILDREN AND ANIMALS!

N/E: Not Established
N/D: Not Determined
N/A: Not Applicable
N/AV: Not Available



Additional Product Information:

While Radiator Specialty Company believes this data is accurate as of the revision date, we make no warranty with respect to the data and we expressly disclaim all liability for reliance thereon. The data is offered solely for information, investigation, and verification. Various government agencies may have specific regulations regarding the transportation, handling, storage, use, or disposal of this product which may not be covered by this MSDS. The user is responsible for full compliance.